

# CASCADIAN<sup>®</sup>

## AcidFIX<sup>™</sup> I

### Automatic Low pH Adjustment Systems

- Raises pH reducing metal leaching and corrosion and improves water taste



#### **CASCADIAN<sup>®</sup> AcidFIX<sup>™</sup> I Automatic pH Adjustment System For Waters With pH 5.0 to 7.0**

- Raise pH
- Reduce Potential Leaching of Copper, Lead and Other Metals Found in Typical Plumbing Systems
- Reduce System Corrosion
- Slower Reacting Than AcidFIX<sup>™</sup> II
- Will Not Over Correct pH
  
- NON-CORROSIVE FIBERGLASS REINFORCED MEDIA TANK
  - Large Dome Hole With Cap To Easily Add Additional Media As Needed
  
- 70-B AUTOMATIC CONTROL VALVE
  - Solid state microprocessor with LED display
  - No memory loss on power out
  - Vacation mode
- Flow rates to 17 GPM (16" Dia. Vessel)
- High Flow 1" or 1.25" Connections and bypass
- Simple backwash regeneration
- Available in black or almond

Note: Equipment Model, Size and Colors May Vary From Photo



✓Protect

✓Prevent

✓Save



# AcidFIX™ I

## Automatic Low pH Adjustment System

<i>CASCADIAN</i> ® AcidFIX™ I					
Part #:	Tank Size (inch)	Height w/Valve (inch)	^Service Rate GPM	*Backwash GPM Cold water (<60°F)	*Backwash GPM Warm Water (>60°F)
ACIDFIXI-09EC	9 X 48	55	2.6 - 5.2	4	6
ACIDFIXI-10EC	10 X 54	61	3.3 - 6.6	5	7
ACIDFIXI-12EC	12 X 52	59	4.7 - 9.4	7	10
ACIDFIXI-13EC	13 X 54	61	5.5 - 11	8	12
ACIDFIXI-14EC	14 X 65	72	6.4 - 12.8	9	13
ACIDFIXI-16EC	16 X 65	72	8.4 - 16.8	12	17

- a) ^Peak service flow rate based on 5 minutes maximum duration.
- b) \*Pump Capacity MUST Meet or Exceed Required Backwash Flow Rate at 25 psi.
- c) A softener may be required after AcidFIX™ I.
- d) Flow rates may be adapted to local conditions.
- e) Media requires periodic replenishing.
- f) Ask your water treatment professional about complete solutions from CASCADIAN®.

**Built with the Best!**

**Built to Last!**

Ask Your Professional *CASCADIAN*® Distributor For Full Warranty Details

**Available From:**