

CASCADIAN[®]

AcidFIX[™] II

Automatic Low pH Adjustment Systems

- Raises pH reducing metal leaching and corrosion and improves water taste



CASCADIAN[®] AcidFIX[™] II Automatic pH Adjustment System

**For Waters With pH 4.5 to 6.0 And Hardness
< 5 grains**

- Raise pH
- Reduce Potential Leaching of Copper, Lead and Other Metals Found in Typical Plumbing Systems
- Reduce System Corrosion
- Faster Reacting Than AcidFIX[™] I
- NON-CORROSIVE FIBERGLASS REINFORCED MEDIA TANK
 - Large Dome Hole With Cap To Easily Add Additional Media As Needed
- 70-B AUTOMATIC CONTROL VALVE
 - Solid state microprocessor with LED display
 - No memory loss on power out
 - Vacation mode
- Flow rates to 17 GPM (16" Dia. Vessel)
- High Flow 1" or 1.25" Connections and bypass
- Simple backwash regeneration
- Available in black or almond

Note: Equipment Model, Size and Colors
May Vary From Photo



✓Protect

✓Prevent

✓Save



AcidFIX™ II

Automatic Low pH Adjustment System

CASCADIAN® AcidFIX™ II					
*Part #:	Tank Size (inch)	Height w/Valve (inch)	^Service Rate GPM	*Backwash GPM Cold water (<60°F)	*Backwash GPM Warm Water (>60°F)
ACIDFIXII-09EC	9 X 48	55	2.6 - 5.2	5	6
ACIDFIXII-10EC	10 X 54	61	3.3 - 6.6	6	7
ACIDFIXII-12EC	12 X 52	59	4.7 - 9.4	8	10
ACIDFIXII-13EC	13 X 54	61	5.5 - 11	10	12
ACIDFIXII-14EC	14 X 65	72	6.4 - 12.8	11	13
ACIDFIXII-16EC	16 X 65	72	8.4 - 16.8	14	17

- a) ^Peak service flow rate based on 5 minutes maximum duration.
- b) *Pump Capacity MUST Meet or Exceed Required Backwash Flow Rate at 25 psi.
- c) Use on waters with less than 5 grains per gallon hardness.
- d) A softener may be required after AcidFIX™ II.
- e) Flow rates may be adapted to local conditions.
- f) Media requires periodic replenishing.
- g) Ask your water treatment professional about complete solutions from CASCADIAN®.

Built with the Best!

Built to Last!

Ask Your Professional CASCADIAN® Distributor For Full Warranty Details

Available From: