



# AcidFIX™

## Automatic Low pH Adjustment Systems

- Raises pH of Acid Water
- Protects Plumbing and Appliances
- Improves Taste
- Self Cleaning - Requires no Salt or Chemicals; No Cartridges to Change



### **CASCADIAN® AcidFIX™ Automatic pH Adjustment Systems**

- Raise pH
- Reduce Potential Leaching of Copper, Lead and Other Metals Found in Typical Plumbing Systems
- Reduce System Corrosion
- Two Systems to choose from:
  - AcidFIX™ I is Slower Reacting and will Not over correct pH
  - AcidFIX™ II is Faster Reacting and corrects lower pH
- No Cartridges to Change
- NON-CORROSIVE FIBERGLASS REINFORCED MEDIA TANK
  - Large Dome Hole With Cap To Easily Add Additional Media As Needed
- 70-BSXT AUTOMATIC CONTROL VALVE
  - Solid state microprocessor with LED display
  - No memory loss on power out
  - Vacation mode
- Flow rates to 17 GPM (16" Dia. Vessel)
- High flow 1", 1.25" or 1.5" connections and bypass
- Simple backwash regeneration
- Available in black or almond

Note: Equipment Model, Size and Colors  
May Vary From Photo



✓Protect

✓Prevent

✓Save



# AcidFIX™

## Automatic Low pH Adjustment Systems

<b>CASCADIAN® AcidFIX™ I</b> Automatic pH Adjustment System For Waters With pH 5.0 to 7.0					
Part #:	Tank Size (inch)	Height w/Valve (inch)	^Service Rate GPM	*Backwash GPM Cold Water (<60°F)	*Backwash GPM Warm Water (>60°F)
ACIDFIXI-09EC	9 X 48	55	2.6 - 5.2	4	6
ACIDFIXI-10EC	10 X 54	61	3.3 - 6.6	5	7
ACIDFIXI-12EC	12 X 52	59	4.7 - 9.4	7	10
ACIDFIXI-13EC	13 X 54	61	5.5 - 11	8	12
ACIDFIXI-14EC	14 X 65	72	6.4 - 12.8	9	13
<b>CASCADIAN® AcidFIX™ II</b> Automatic pH Adjustment System For Waters With pH 4.5 to 6.0 And Hardness < 5 grains					
Part #:	Tank Size (inch)	Height w/Valve (inch)	^Service Rate GPM	*Backwash GPM Cold Water (<60°F)	*Backwash GPM Warm Water (>60°F)
ACIDFIXII-09EC	9 X 48	55	2.6 - 5.2	5	6
ACIDFIXII-10EC	10 X 54	61	3.3 - 6.6	6	7
ACIDFIXII-12EC	12 X 52	59	4.7 - 9.4	8	10
ACIDFIXII-13EC	13 X 54	61	5.5 - 11	10	12
ACIDFIXII-14EC	14 X 65	72	6.4 - 12.8	11	13
ACIDFIXII-16EC	16 X 65	72	8.4 - 16.8	14	17

- a) ^Peak service flow rate based on 5 minutes maximum duration.
- b) \*Pump Capacity MUST Meet or Exceed Required Backwash Flow Rate at 25 psi.
- c) A softener may be required after the AcidFIX™ system to reduce added hardness.
- d) Flow rates may be adapted to local conditions.
- e) Media requires periodic replenishing.
- f) For the AcidFIX™ II, untreated water must have less than 5 grains per gallon hardness.
- g) Ask your water treatment professional about complete solutions from CASCADIAN®.

**Built with the Best!                      Built to Last!**

Ask Your Professional *CASCADIAN®* Distributor For Full Warranty Details

**Available From:**